

Valve Clean

Description

Valve Clean is an ash-free, self-mixing combination of active agents, formulated according to the latest additive and fuel technologies. Specifically developed for port injection fuel systems.

Effect:

- breaks down deposits on valves and in the combustion chamber
- removes and dissolves residues throughout the fuel system
- protects against corrosion throughout the fuel system
- environmentally friendly and economical
- prevents carburettor icing
- proven performance with catalytic converters and turbochargers

Properties

- reduces deposits
- reduces residues
- good corrosion protection
- compatible for the use with turbochargers and catalytic converters
- burns ash-free
- environmentally friendly
- economical
- prevents carburetor icing

Technical data

Color / appearance	hellbraun / light brown
Density at 59 °F	0,809 g/ml DIN 51757
Flash point	145 °F DIN ISO 2592
Pour point	< -40 °F DIN ISO 3016
Viscosity at 104 °F	<7 mm ² /s
Form	flüssig / liquid
Odor	charakteristisch / characteristic

Areas of application

For all gasoline engines (carburetor and fuel-injection engines).

Application

For best results add Valve Clean to gasoline at each filling. One 150 ml can of Valve Clean treats 75 liters (20 gal.) of gasoline. Minimum fuel filling of 25 liters (7 gal.) is requested for optimum product performance.



Comment

WARNING: Cancer- www.P65Warnings.ca.gov

Available pack sizes

150 ml Can sheet metal	2001 USA (-EN-)
150 ml Can sheet metal	7701 CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.