LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Service-hotline: 0800/8323230 Technical hotline: +49 (0)731/1420-871 www.liqui-moly.de

Description

Fully synthetic motor oil for extreme conditions. Operating with the widerange viscosity 10W-60. It provides high thermal stability. Lubrication is also reliably maintained at extreme operating conditions. Optimizes engine performance. Developed for the demands of high performance power units.

Synthoil Race Tech GT1 SAE 10W-60

Properties

- outstanding engine cleanliness
- mixable with most engine oils
- high lubrication reliability
- tested for the use with catalytic converters

Product information

- optimum stability to aging
- optimum lubrication in extreme operating conditions
- instant lubrication after cold start
- extremely low oil consumption
- extremely low evaporation loss

Specifications and approvals: ACEA A3 • ACEA B4 • API SN

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Fiat 9.55535-H3

Technical data

SAE class (engine oils)	10W-60 SAE J300
Density at 59 °F	0,855 g/cm³ DIN 51757
Viscosity at 104 °F	168 mm²/s ASTM D 7042-04
Viscosity at 212°F	24,0 mm²/s ASTM D 7042-04
Viscosity at -22 °F (MRV)	< 60000 mPas ASTM D4684
Viscosity at -13 °F (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	174 DIN ISO 2909
HTHS at 302 °F	>= 3,5 mPas ASTM D5481
Pour point	-33 °F DIN ISO 3016
Evaporation loss (Noack)	5,3 % CEC-L-40-A-93

Technical data

Flash point	475 °F DIN ISO 2592
Total base number	10,5 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	3,5 DIN ISO 2049

Areas of application

For gasoline and diesel engines, particularly suitable for use in motorsport and other high performance applications where a motor oil according to the existing product specification is required. LIQUI MOLY recommends this motor oil for specific BMW M-series vehicles up to MY 2010. Safe for catalytic converters and turbochargers.

Application

Observe manufacturers instructions.

Available pack sizes

1 l Canister plastic	2068 USA AND CANADA (-EN- F-)
5 l Canister plastic	2024 USA AND CANADA (-EN- F-)
20 l Canister plastic	20127 USA AND CANADA (-EN- F-)
60 l Drum sheet metal	20374 USA AND CANADA (-EN- F-)
205 l Drum sheet metal	20375 USA AND CANADA (-EN- F-)
1000 l Container	1772 D-GB





PI 36/06/05/2020

PI 36/06/05/2020

Product information Synthoil Race Tech GT1 SAE 10W-60



Our information is based on thorough research and may be considered reliable, although not legally binding.